

DIGITUS® Line-Interactive UPS, 2000VA/1200W



✓ 4x Schuko output

✓ 2-6 ms transfer time (10 ms max.)

✓ Fast charge (90% in four hours)

✓ Backup time: 10-12 mins

Abstract

DIGITUS® Line-Interactive UPS, 2000VA/1200W, 12V/9Ah x 2 battery, 4x Schuko output, LCD display

Features

- Capacity: 2000VA/1200W
- Input voltage: 230VAC
- Voltage range: 162-290 VAC
- Frequency range: 50 Hz (auto sensing)
- Output voltage: 230 VAC \pm 10%
- AC voltage regulation (battery mode): 10%
- Frequency range (battery mode): 50 Hz \pm 1%
- Typical transfer time: 2-6 ms
- Waveform (battery mode): Simulated sine wave
- Battery: 12V/9Ah x 2
- Typical recharge time: 4 hours to recover 90% of capacity
- with overload-, discharge- and overcharge protection
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Alarm sounds: Battery mode (sounding every 10 sec.), low battery (sounding every second), overload (sounding every 0.5 sec.), fault (continuously sounding)
- Dimensions (HxWxD): 205x397x146 mm
- Net weight: 11.5 kg
- Humidity: 0-90% RH @ 0 °C to +40 °C (non-condensing)
- Noise level: Less than 40 dB

Product Overview

The DIGITUS® Line-Interactive UPS come with a compact size and an excellent microprocessor control, which guarantees high reliability. With an user friendly operation they provide high performance protection for your business and office computer systems against data loss and damage. Features like overload-, discharge- and overcharge protection, cold start functions and energy saving features, as well as an acoustic alarm system are just a few advantages of the DIGITUS® Line-Interactive UPS units.

DIGITUS® Line-Interactive UPS, LED display

DN-170013-1 DIGITUS® Line-Interactive UPS, 600VA/360W, 12V/7Ah x 1 battery, 2x Schuko, AVR, RJ-11, LED display

DIGITUS® Line-Interactive UPS, LCD display

DN-170024-1 DIGITUS® Line-Interactive UPS, 1000VA/600W, 12V/7Ah x 2 battery, 4x Schuko, AVR, USB, RS232, RJ11/RJ45, LCD display

DN-170025-1 DIGITUS® Line-Interactive UPS, 1500VA/900W, 12V/9Ah x2 battery, 4x Schuko, AVR, USB, RS232, RJ-11/45, LCD display

DN-170026-1 DIGITUS® Line-Interactive UPS, 2000VA/1200W, 12V/9Ah x 2 battery, 4x Schuko, AVR, USB, RS232, RJ-11/45, LCD display

Product Images

