



## USB Car Charger



**Manual**

84100

## **DESCRIPTION:**

Quickly and efficiently charge your smartphones, tablets, cameras, and other mobile devices while on the move in your car. The ednet USB Car Charger can charge up to two devices at once. Its total output of 3.4A (1A, 2.4A) also makes it possible to quickly and efficiently charge tablets. Despite this output power, the housing is still small, ensuring it fits in every car, mobile home, etc.

## **FEATURES:**

- Compact design
- USB Max. 5V2.4A fast charge
- Support multiple devices power charging ( 5V2.4A and 5V1A)
- Auto adjust power current requirement.
- Multiple protection: overcharge, overvoltage, short circuit , overcurrent and overload protection
- Good compatibility to the market most vehicle equipment
- Support12V-24V wide voltage
- Fireproof PC material, fire retardant, anti-corrosion, anti-fall, hard practical, double insulated to prevent current interference
- Stainless steel shrapnel buckle bit, long life time, good quality assurance

## **HOW TO USE:**

1. Plug the USB car charger 84100 into the cigarette lighter port or the vehicle's power outlet.
2. The power indicator of 84100 will be lighten up
3. Plug the USB cable of power devices into the charger

## **SPECIFICATIONS:**

- Input voltages: 12-24V DC
- USB output voltage: 5V DC
- Total USB output current: 3.4A max
- USB ports: 1x 1A, 1x 2.4A
- CE, FCC, RoHS
- USB car charger for all smartphones, tablets, cameras, iPhone®, iPad® etc.
- LED Power light indicator

## **WORKING ENVIRONMENTAL:**

- Operating temperature: 0 to 40°C
- Storage temperature: -20 to 85°C
- Operating humidity: 15 to 85% RH
- Storage humidity: 5 to 95% RH

## **PROTECTIONS:**

- Over-charge protection
- Over-voltage protection
- Short-circuit protection
- Over-current protection
- Overload protection

Note: If wrongly installed or improperly used in the living area, the device can cause interference in radios and other electronic devices. Appropriate use is when the device, as far as feasible, is operated with shielded connection cables (with network products in addition to category 5 shielded cables and higher). The device has been tested and falls within the limits of class B computing equipment according to the requirements of EN 55022.

Warning: This device conforms with test category B - it can cause radio interference in the living area; in this case the operator may demand that appropriate measures are implemented and arise for this reason. Declaration of conformity: The device fulfills the EMV requirements according to EN 55022 for ITE and EN 55024. Devices with external or integrated power supply furthermore fulfill the requirements of EN 61000-3-2 and EN 61000-3-3. In this way, the fundamental protection requirements of the EMV-2004/108/EC guideline are fulfilled. The CE conformity has been proven. The pertinent declarations are deposited with the manufacturer.

**www.assmann.com**  
ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
58513 Lüdenscheid  
Germany

