



## **USB CAR CHARGER, 2 Port**

**Manual**

**84118**

## **SPECIFICATIONS:**

- Input voltages: 12-24V DC
- USB output voltage: 5V DC
- Total USB output current: 3.1A max
- USB ports: 1x 1A, 1x 2.1A
- CE, FCC, RoHS
- USB car charger for all smartphones, tablets, cameras, iPhone®, iPad® etc.
- This car charger is with fuse, short circuit protection, LED light indicator

## **HOW TO USE:**

- Plug the USB car charger 84118 into the cigarette lighter port or the vehicle's power outlet.
- The power indicator of 84118 will be lighten up
- Plug the USB cable of music player or devices what you wanted to charge into the charger

## **FEATURES:**

- Certification: CE
- With RoHS Directive-compliant
- Light and convenient plug-in
- LED indication
- High efficiency
- High reliability

## **WORKING ENVIRONMENTAL:**

- Operating temperature: 0 to 40° C
- Storage temperature: -20 to 65° C
- Operating humidity: 10 to 95% RH
- Storage humidity: 10 to 95% RH

## **PROTECTIONS:**

- Over-voltage protection
- Over-current protection
- Short-circuit protection
- Overload protection

**DESCRIPTION:**

- Built-in IC chip, 100% full loading burning test
- 2.1A for tablet PCs, 1A for smartphones, cameras, etc.
- Wide input voltage range
- Compact size and lightweight